

MS100

Management server for large setups



PRODUCT SPECIFICATIONS**MS100**

RAID	RAID 1 / RAID 10
Network interface	(2) 10/100/1000 BaseT
Dimensions WxDxH	17.20 x 9.80 x 1.75 inch / 43.69 x 24.89 x 4.45 cm
Storage	500 GB - Hot swappable HDD
Weight	38.0 lbs / 17.3 kg
Power supply	280 W
Avg Power Consumption	85 W
V2D	Video-to-data (V2D)
RTP	H.264, MPEG-4, AAC
UDP	DIS
MPEG-TS	MPEG-2
Networking protocol	Unicast - multicast (IGMP)
Management Interface	Admin interface, console
Console Interface	VGA, serial, telnet, SSH
Data Configuration storage	Removable CF card
Operating temperature	10° to 35° C
Operating relative humidity	10% to 90% non-condensing
Networking	Media connection control, advanced media routing, NTP server synchronization, network address translation (NAT)
Reliability	Redundancy, self-healing (maintains connection through node failure), scheduled database backup
Security	Policy-based access: per-user, per-device, connections, assets, media access control, user activity logging
Remote access	Adjust or manipulate window layout from any location
Certification and compliance	<ul style="list-style-type: none">■ Safety: UL / CSA / EN / IEC 60950-1■ EMC: CE, FCC Part 15 Class A

Last updated: 08 Jun 2016

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.