

# UDX-4K32

31,000 lumens, 4K UHD, 3-chip DLP laser phosphor large venue projector



- **Quicker installation, lower costs, optimal asset management**
- **Unmatched colors, 4K resolution, and best-in-class processing**
- **Unbelievable experiences thanks to exceptional performance**
- **24/7 operation**

The UDX range delivers stunning experiences and savings on installation and shipping time, reducing costs significantly. The most compact, high-brightness laser projectors with integrated cooling on the market, the UDX projectors bring reliable and razor-sharp 4K images to every type of event and venue.

The UDX-4K32 features 4K UHD resolution and 31,000 lumens light output to ensure flawless shows with accurate colors at all times. The Constant Light Output (CLO) functionality also guarantees peace of mind by providing constant brightness and color over time. The UDX platform offers the widest color spectrum in the industry. Without compromising on brightness, the UDX color quality matches the renowned Xenon quality and outperforms the Rec. 709 color space.

#### **Cut costs with laser projection**

Thanks to their laser phosphor light source, lamp-related costs and maintenance as well as image flicker, belong to the past. The UDX series delivers a long lifetime and high reliability to ensure minimum downtime. The UDX's compact and rugged design allows you to reduce shipping and labor costs. The modular components can be removed quickly to limit servicing time. You can also reuse your TLD+ lenses.

#### **Pick your brightness and resolution**

The unique FLEX<sup>2</sup> feature will allow you to tune and lock your brightness and resolution to a specific show. You'll now need less projectors to cover a wider range of brightness levels and resolutions.

#### **Faster processing for sharper images**

The Barco Pulse 4K electronics offer an intuitive interface and flexible, user-friendly, embedded control software. Its Single Step Processing (SSP) allows for sharper images and less latency.

**PRODUCT SPECIFICATIONS****UDX-4K32**

|                                    |  |
|------------------------------------|--|
| Projector type                     | 4K UHD 3-chip DLP digital projector  |
| Technology                         | 0.9" DMD™ x3   |
| Resolution                         | 3,840 x 2,400 (4K UHD) / 2,560 x 1,600 (native)  |
| Brightness                         | 31,000 (WQ)/30,000 (4K UHD) center lumens* / 30,000 ansi lumens  |
| Contrast ratio                     | 2,000:1  |
| Brightness uniformity              | 95%  |
| Aspect ratio                       | 16:10  |
| ScenergiX                          | Horizontal and vertical edge blending  |
| Lenses                             | TLD+ 0.37, 0.65-0.85, 0.8-1.16:1 ; 1.25-1.6:1 ; 1.5-2.0:1 ; 2.0-2.8:1 ; 2.8-4.5:1 ; 4.5-7.5:1 ; 7.5-11.5:1 |
| Optical lens shift                 | V: -100% to +130% / H: +/-40% on zoom lenses (memorized)   |
| Color correction                   | P7   |
| Light source                       | laser phosphor with inorganic phosphor wheel   |
| Light source lifetime              | 25,000 hrs   |
| Optical dowser                     | Digital  |
| Picture-in-picture                 | Two sources simultaneously   |
| Orientation                        | 360°   |
| Sealed DLP™ core                   | standard   |
| DMX 512                            | standard   |
| WARP                               | Direct adjust OSD + toolset  |
| Image processing                   | Embedded warp & blend  |
| Keystone correction                | Yes  |
| Integrated web server              | Yes  |
| CLO (constant light output)        | Standard   |
| 3D                                 | Active eye wear (optional), passive circular (optional); 2 flash up to 200Hz*                              |
| Inputs                             | Single HDBaseT; HDMI 2.0 (HDCP 2.2); DP 1.2 (HDCP 1.3); Quad 3G/12G SDI / BarcoLink                        |
| Optional Inputs                    | Quad DP1.2   |
| Input resolutions                  | From NTSC up to 4K (4,096 x 2,160)   |
| Max. pixel clock                   | 600 MHz  |
| Software tools                     | Projector Toolset + Android** app + iOS** app  |
| Control                            | XLR wired + IR, RS232, Wifi** (opt), GSM** (opt)   |
| Network connection                 | 10/100 base-T, RJ-45 connection, Wifi** (optional)   |
| Power requirements                 | 120-160 V (reduced power) / 200-240V (+/-10%), 20A, 50-60Hz  |
| Max. power consumption             | 2,900W nom/3,100W max / STBY less than 10W   |
| Noise level (typical at 25°C/77°F) | 52dB(A)  |
| Operational ambient temperature    | 0-40°C / 32°-104°F   |
| Operational humidity               | 0-80% (non condens)  |
| Dissipation BTU                    | Max. 9,895 BTU/h   |
| Dimensions (WxLxH)                 | 660 x 830 x 350 mm / 25.98 x 32.67 x 13.77 inches  |
| Shipping Dimensions                | (LxWxH) 1,200 x 800 x 685 mm / 47.24 x 31.49 x 26.96 inches  |
| Weight                             | 92kg (202 lbs)/shipping weight from factory: 110kg (242 lbs)   |

**PRODUCT SPECIFICATIONS****UDX-4K32**

---

|                      |  |
|----------------------|--|
| Standard accessories | Power cord, wireless/XLR wired rugged remote control   |
| Certifications       | Compliant with UL60950-1 and EN60950-1 complies with FCC rules & regulations, part 15 Class A and CE EN55032 Class A, Rohs |
| Warranty             | 3 years  |
| *                    | +/-10%   |

---

**Last updated: 06 Nov 2018**

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.