

4K60 Tri-Combo output card



- Full quality 4K@60p 4:4:4 on a single cable
- Support for output rotation of 90, 180, or 270 degrees
- Rugged modular design
- One DisplayPort 1.2 connector
- Supports up to 4K60p
- HDCP 1.4 Compliant
- Automatic Output acquisition and configuration
- Support for VESA/CEA, and custom timings
- One HDMI 2.0 Connector
- Supports up to 4K60p
- HDCP 2.2 compliant
- Automatic Output acquisition and configuration
- Support for VESA/CEA, and custom timings
- Four 12G-SDI (BNC) Connectors
- Supports up to 4x 1200p@60, or 2x 4K@60p/ UHD per card (single cable)

PRODUCT SPECIFICATIONS**4K60 TRI-COMBO OUTPUT CARD**

Connectors	1x DP 1.2; 1x HDMI 2.0; 4x 12G-SDI (BNC)
Resolution	up to 2x 4096x2160@60p
Color depth	8-bit; 10-bit; 12-bit (DL or lower)
Color sampling	HDMI 2.0: up to UHD@60p 4:4:4 8-bit DP1.2: up to UHD@60p 4:4:4 10-bit 12G-SDI: up to UHD@60p 4:2:2 10-bit
HDCP	HDCP 2.2 compliant on HDMI HDCP 1.x compliant on DisplayPort
Signal capacity	HDMI: 600 MHz DisplayPort: 660MHz
Features	Rotation and splitter mode

Last updated: 05 Jul 2021

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.