

TruePix TP1.9-E

1.9 mm pixel pitch, high-res indoor LED display for mid-brightness applications



- **Smart engineering guarantees truly seamless outcomes**
- **Smooth and efficient operations, 24/7**
- **Superb color accuracy, under all lighting conditions**
- **Reduced ecological footprint**
- **5 years of dedicated service and support**

TruePix TP1.9-E is Barco's new flagship indoor high-resolution LED platform. The 27.5" inch tiles, with a 16:9 aspect ratio, have a pixel pitch of 1.9 mm. TruePix is designed for control room, corporate and broadcast visualization applications and supports both environments exposed to ambient light and controlled lighting environments.

Truly seamless outcomes

TruePix sets a new standard for the LED video wall experience based on decades of experience. The solution brings content to life as intended and ensures predictable, truly seamless outcomes, by combining smart engineering and Infinipix® Gen2, the next generation of Infinipix®. Smooth and efficient operations are guaranteed 24/7, next to full peace of mind.

Barco TruePix' smart engineering introduces a unique mechanical concept for risk-free and precise installations, eliminating visual distortion. This unmatched seamlessness and flatness are achieved through guided module placement and self-leveling mounts. The next generation of Barco's proprietary Infinipix® processing – Infinipix® Gen2 – guarantees full image integrity at any brightness level, together with superb color accuracy. It flexibly and automatically supports any content need while reducing eye fatigue.

Peace of mind at any time

Smooth and efficient operations are guaranteed 24/7 through uninterrupted data flows. Users can reduce the carbon footprint by using the EcoPower standby mode. 5 years of dedicated service and support (ensuring a uniform viewing experience) and remote cloud-based video wall management, allow for peace of mind during the entire product lifetime.

PRODUCT SPECIFICATIONS**TRUEPIX TP1.9-E**

Pixel pitch	1.906
Pixel per module	320x180 (HxV)
LED lifetime	100,000h (video -50% brightness)
Brightness	>600 nit
Internal processing	23 bit
Color depth	16 bit (281 trillion colors)
Shaders	No
Control	Infinipix® Gen2
Refresh rate	3,840 Hz
Frame rate	24 / 25 / 29.97 / 30 / 47.95 / 48 / 50 / 59.94 / 60 / 100 / 119.88 / 120 / 144 / 240 Hz
3D	3D supported
Hor. viewing angle	160° +/-5°
Vert. viewing angle	160° +/-5°
Brightness uniformity	>98%
Dimming	0-100%
Contrast	>7,000:1
Power consumption	547 W/m ² (max) 238 W/m ² (typ)
Heat dissipation	1,865 BTU/h/m ² (max) 812 BTU/h/m ² (typ)
Operation power voltage	100-240V 50/60Hz
Operational temperature	-10°C to +40°C / 14°F to 104°F
Operational humidity	10 -80%
IP rating	IP30
Redundancy	Power: Optional Data: Inter-tile and signal loop redundancy embedded / N + N redundancy optional
HDR	HLG / HDR10 supported
Concave curvature	Up to 5° inter tile for standard and camera curved frame
Convex curvature	Up to 3° inter tile for standard curved frame Convex curving is not applicable for camera curved frame
Dimensions	(WxHxD) 609.92x343.08x71mm / 24.01"x13.5"x2.80"
Weight	8.2kg/tile (single PSU) 8.6 kg/tile (dual PSU)
Serviceability	Full front & full back service
Cable management	No external cabling
Installation	Self-leveling with surface tolerance compensation
Module replacement	Automated parallel motorized extraction
Module placement	Guided module placement
Seam quality	Guaranteed seamless
Flatness -lay flat quality	Guaranteed flatness
Ergonomics	Driver algorithm to reduce eye fatigue
Certifications	CE, UL, FCC class A, RoHS, WEEE, REACH, CCC, RCM
Warranty	3 years
SmartCare / EssentialCare service offering	5 years

Last updated: 01 Jun 2022

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.