

iD NR-6

Network-centric, SXGA+, 6,000 lumens single-chip DLP projector



PRODUCT SPECIFICATIONS**ID NR-6**

Light output	6,000 ANSI lumens
Contrast	2,000:1
Resolution	1400x1050 SXGA+
Chip type	Single-chip DLP with BrilliantColor processing
Lamp	2x250W UHP
Lamp lifetime	1,500 hrs per lamp
Weight	12,9kg (28,5lbs) / 17,5kg (38,5lbs) shipping weight
Dimensions (WxLxH)	195mm x 415mm x 590mm / 7"68 x 16"34 x 23"23
Lens Shift Vertical	-30% to +110%
Inputs	<ul style="list-style-type: none">■ 1x 5-BNC: RGBHV, component video■ 1x composite video (BNC)■ 1x S-video■ 1x VGA (D15 connector)■ 1x DVI-D Optional SDI input
Communication Port	1x RS232
Video	<ul style="list-style-type: none">■ PAL, SECAM, NTSC signals■ Composite, S-video, component or RGB formats■ All current HDTV standards (720i, 720p, 1080i, 1080p)
Data	<ul style="list-style-type: none">■ DVI sources up to SXGA+■ Apple Macintosh formats■ Electronic workstations with a resolution of up to 1600x1200 / 75Hz■ All computer graphics formats up to UXGA / 75 Hz
Scan Frequencies	<ul style="list-style-type: none">■ Horizontal 15kHz - 110Hz■ Vertical 25Hz - 150Hz
Safety Regulations	Compliant with UL1950 and EN1950
Electromagnetic Interference	Compliant with FCC rules and regulations
AC power	90-254 VAC / 50-60Hz
Max. power consumption	2,400 BTU/h
On board display server	<ul style="list-style-type: none">■ Pentium M 1.6GHz processor■ 512 MB RAM, 40GB hard disk■ Microsoft Windows XP multi-language OS■ Barco source and layout selection software■ Barco centralized control and maintenance software

Last updated: 21 Jan 2018

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.