

# D320 PL

Advanced image processing unit that allows you to control up to 4 sources on one LED or Projection display.



**PRODUCT SPECIFICATIONS****D320 PL**

<b>Inputs</b>	4 optional inputs Front accessible Integrated video processing Auto sensing, hot swappable s-video, composite, YUV/RGB SDI, HD-SDI, DVI up to UXGA
<b>Compatibility</b>	Barco LED Displays & projectors
<b>Output</b>	DVI-A, DVI-D
<b>Scalability</b>	Chaining for more inputs Stacking for more displays
<b>Flexibility</b>	User defined inputs
<b>Effects</b>	Anamorphic imaging Chroma-keying [per input] Alpha-keying [per input] Z-order control Windowing/ View ports
<b>Weight</b>	+/-7 kg
<b>Operating T°</b>	0°C <-> 45°C
<b>Power</b>	120W max auto ranging 90-264V (50-60 Hz) Connector: 3 pin IEC
<b>Order Information</b>	R9851550
<b>Connectors</b>	RS 232 [RJ11]
<b>Control</b>	through XLite toolset
<b>Scaler</b>	4 input channels [Data-Video] fully scalable to desired output resolution
<b>Size</b>	482mm x 53mm x 486mm
<b>Size Input Units</b>	103mm x 41mm x 181mm
<b>Window Positioning</b>	Intuitive positioning interface
<b>Z-order control</b>	Instant modification of Z-order control, for each output window

Last updated: 26 Nov 2019

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.