

RLM R6+ Performer

<P>SXGA+, 6,000 lumens three-chip DLP projector</P>



ESPECIFICACIONES TÉCNICAS**RLM R6+ PERFORMER**

| | |
|----------------------------|--|
| Light output | 6500 Center lumen 6000 ANSI Lumen |
| Resolution | 1400 x 1050 (native) |
| Brightness uniformity | > 90% for the total screen |
| Contrast ratio | 1600:1 (full field) |
| Display | 3 Chip DLP SXGA+ (resolution of 1400 x 1050 pixels (aspect ratio 4:3)). |
| Convergence | Max allowed convergence drift is 0.5 pixel. This is checked on vertical and horizontal midlines only. Corners are not applicable for convergence error. This is measure with TLD 1.2 lens on axis. |
| Features | <ul style="list-style-type: none">▪ AutoImage▪ Advanced picture-in-picture▪ Seamless switching with effects▪ Standard light shutter▪ Advanced digital zoom▪ Rigging point▪ Carrying handle▪ Frame▪ P7 color processing |
| Picture-in-picture | Up to 4 sources simultaneously (2 data, 1 video and 1 SDI) |
| Inputs | Fixed inputs <ul style="list-style-type: none">▪ 1x Configurable 5-Wire (BNC)▪ 1x Composite Video (BNC)▪ 1x S-Video (4-pin mini-DIN)▪ 1x analogue RGB (D15 connector)▪ 1x SDI/HDSDI (+ loop through)▪ 1x DVI (Digital Visual Interface) |
| Outputs | HDSDI/ SDI loop out |
| Communication | <ul style="list-style-type: none">▪ 1x RS-232C IN (D-9 connector)▪ 1x RS-232C OUT (D-9 connector)▪ 1x RS-232C IN (XLR connector)▪ mini-jack for wired remote control |
| Compatibility | <ul style="list-style-type: none">▪ All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats▪ All currently proposed HDTV, extended and improved television standards (1080i, 720p)▪ All computer graphics formats from VGA, SVGA, XGA, SXGA,full HD to UXGA▪ Most Macintosh computers▪ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz▪ Most computer sources with a pixel clock up to 200 MHz▪ DVI sources up to SXGA+ |
| Input source compatibility | 1600 x 1200 (max. input) |
| Screen size | From 1-7m / 3-23ft.recomended |
| Scan Frequencies | Pixel clock >162Mhz (UXGA 60hz) |
| Network connection | Optional (10 base-T) |
| Ambient temperature | Max 40°C (104°F) |
| Lamp | 2 x 250 W mercury Lamp warranty: 1000 hrs |

ESPECIFICACIONES TÉCNICAS**RLM R6+ PERFORMER**

| Lenses | Lens | Order Nr |
|-------------------------------------|--|----------|
| | TLD (HB) 0.8 | R9842040 |
| | TLD (HB) 1.6 - 2.0 | R9842060 |
| | TLD (HB) 2.0 - 2.8 | R9842080 |
| | TLD (HB) 2.8 - 5.0 | R9842100 |
| | TLD (HB) 5.0 - 8.0 | R9842120 |
| Lens Shift | Vertical: -10% to +110% Horizontal: -50% to +50% (small differences occur per lens type) | |
| Lens encoders | On zoom and focus (with TLD lenses) | |
| ScenergiX | Standard horizontal and vertical electronic edge blending | |
| Sealed DLP™ core | Standard | |
| Dust filters | Metal filters | |
| Noise Level | 42 dB(A) (at 40°C) | |
| Mains Voltage | 92-240 V / 50 -60 Hz | |
| Power consumption | 700 W | |
| Power Dissipation | Max 2217 BTU/h | |
| AC power | 90V -255V (50 Hz -60Hz) | |
| Weight | Projector: 25 kg (56 lbs) Frame: 5 kg (11 lbs) | |
| Dimensions | W x L x H 705 x 707,8 x 316,5 mm (27,8 x 27,9 x 12,5 inch) | |
| Shipping Dimensions | Width: 56 cm Height: 100 cm Depth: 100 cm Floor Space: 1 m ² Volume: 0,56 m ³ Gross Weight: 65 kg | |
| Safety Regulations | Compliant with UL1950 and EN60950 | |
| Electromagnetic Interference | Complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A | |
| Order Information | Projector body (without lens): R9010270 Spare dual lamp: R9852940 | |

Generado en: 21 Jan 2018

Las especificaciones técnicas pueden estar sujetas a cambios sin previo aviso. Consulte www.barco.com para obtener la información más actual.