

# iQ Praxis G300



**TECHNICAL SPECIFICATIONS****IQ PRAXIS G300**

Salida de luz	3,500 ANSI lumen
brillo uniforme	Brightness uniformity: >95 % for the total screen
Paneles LCD	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
resolución	1024 x 768 (native)
lámpara	2x 200 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1500 h/lamp. 1500 hours in Dual Lamp Mode or max. 3000 hours/set in Single Lamp Mode.
lentes	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
tamaño de pantalla	From 1-6 m/3-20 ft.
contraste	>400 : 1 (full white/full black)
frecuencias de barrido	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
compatibilidad	The IQ Praxis G300 is compatible with: <ul style="list-style-type: none"><li>• All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>• All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>• All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>• Most Macintosh computers</li><li>• Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>• Most computer sources with a pixel clock up to 160 MHz</li><li>• DVI sources up to SXGA</li></ul>
entradas	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video , RGBHV, RGBS, RGsB. 1x Composite Video (BNC) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
dimensiones (ancho x largo x alto)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
comunicación	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
nivel de ruido	
corriente alterna	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
consumo de potencia	Max 520 Watt
disipación de potencia	Max 1775 BTU/h
peso	Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight: <ul style="list-style-type: none"><li>• without lens max.17.5 kg / 38.5 lbs.</li><li>• with lens: max.20 kg / 44 lbs.</li></ul>
desplazamiento de lente	QVD Lenses Motorized V shift: -30% +120%

Generado en: 21 Jan 2018

Las especificaciones técnicas pueden estar sujetas a cambios sin previo aviso. Consulte [www.barco.com](http://www.barco.com) para obtener la información más actual.