

# iQ G210L



**TECHNICAL SPECIFICATIONS****IQ G210L**

<b>Salida de luz</b>	2,200 ANSI lumen
<b>brillo uniforme</b>	Brightness uniformity: >95 % for the total screen
<b>resolución</b>	1024 x 768 (native)
<b>Paneles LCD</b>	3 active matrix 1.4" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
<b>lámpara</b>	2x 120 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 6000 h/lamp. 6000 hours in Dual Lamp Mode or max. 12000 hours/set in Single Lamp Mode.
<b>lentes</b>	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
<b>tamaño de pantalla</b>	From 1-6m/3-20ft.
<b>contraste</b>	>800:1 (full white/full black)
<b>frecuencias de barrido</b>	Horizontal 15kHz -110kHz Vertical 25 Hz -150 Hz
<b>características</b>	<ul style="list-style-type: none"> <li>• Advanced picture-in-picture</li> <li>• Seamless switching with effects</li> <li>• Standard cable basket</li> <li>• Standard light shutter</li> <li>• Advanced digital zoom</li> </ul>
<b>compatibilidad</b>	<p>The IQ G210L is compatible with:</p> <ul style="list-style-type: none"> <li>• All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li> <li>• All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li> <li>• All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li> <li>• Most Macintosh computers</li> <li>• Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li> <li>• Most computer sources with a pixel clock up to 160 MHz</li> <li>• DVI sources up to SXGA</li> </ul>
<b>entradas</b>	<p>1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB</p> <p>1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board)</p> <p>1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's)</p> <p>1x VGA (D15 connector)</p> <p>1x DVI (Digital Visual Interface)</p>
<b>dimensiones (ancho x largo x alto)</b>	<p>Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D)</p> <p>Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)</p>
<b>comunicación</b>	<p>1x D9 connectors for RS232 In/Out</p> <p>1x spherical IR receiver</p>
<b>nivel de ruido</b>	
<b>corriente alterna</b>	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
<b>consumo de potencia</b>	Max 350 Watt
<b>disipación de potencia</b>	Max 1195 BTU/h
<b>regulación de seguridad</b>	Compliant with UL1950 and EN60950
<b>interferencia electromagnética</b>	Barco's IQ G210L complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
<b>peso</b>	<p>Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight:</p> <ul style="list-style-type: none"> <li>• without lens max.17.5 kg / 38.5 lbs.</li> <li>• with lens: max.20 kg / 44 lbs</li> </ul>
<b>desplazamiento de lente</b>	<p>QVD Lenses</p> <p>Motorized V shift: -30% +110%</p> <p>For specific details per lens type: see lens product pages</p>
<b>Conmutación fluida</b>	Standard
<b>conexión de red</b>	Refer to IQ Pro G210L

Generado en: 21 Jan 2018

Las especificaciones técnicas pueden estar sujetas a cambios sin previo aviso. Consulte [www.barco.com](http://www.barco.com) para obtener la información más actual.