

# SLM R9+ Performer

Compact, SXGA+ resolution and 9000 Ansi Lumen light-output.



**TECHNICAL SPECIFICATIONS****SLM R9+ PERFORMER**

Salida de luz	9000 ANSI Lumens 9500 Center Lumens
resolución	1400 x 1050 (native)
brillo uniforme	> 90% for the total screen
relación de contraste	1600 : 1 (full field)  High contrast mode: 2000 : 1
pantalla	3 Chip DLP SXGA+ (resolution of 1400 x 1050 pixels (aspect ratio 4:3)).
características	<ul style="list-style-type: none"><li>▪ Picture in picture</li><li>▪ Seamless switching with effects</li><li>▪ Standard light shutter</li><li>▪ Rigging point</li><li>▪ Carrying handle</li><li>▪ High contrast mode</li><li>▪ P7 color processin</li></ul>
Imagen dentro de la imagen	2 sources simultaneous
entradas	Fixed inputs <ul style="list-style-type: none"><li>▪ 2x Configurable 5-Wire (BNC; incl. 2 video decoders)</li><li>2x DVI (Digital Visual Interface)</li></ul> Modular inputs Standard: <ul style="list-style-type: none"><li>▪ 1x SDI (+ loop through)</li></ul> Optional: <ul style="list-style-type: none"><li>▪ 1x HDSDI (+ loop through)</li></ul>
salidas	DVI out (1400 x 1050) of full screen composed image
comunicación	<ul style="list-style-type: none"><li>▪ 1x RS-232C IN (D-9 connector)</li><li>▪ 1x RS-232C OUT (D-9 connector)</li><li>▪ 1x RS-232C IN (XLR connector)</li><li>▪ 1x 2way prop. protocol to Rugged remote (5 pins XLR connector)</li><li>▪ 1x prop. protocol (RJ45 connector)</li><li>▪ mini-jack for wired remote control</li></ul>
compatibilidad	· All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats · All currently proposed HDTV, extended and improved television standards (1080i, 720p) · All computer graphics formats from VGA, SVGA, XGA, SXGA, full HD to UXGA · Most Macintosh computers · Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz · Most computer sources with a pixel clock up to 200 MHz · DVI sources up to SXGA+
Compatibilidad de fuentes de entrada	max. input: up to 1920 x 1080 and 1600 x 1200
tamaño de pantalla	From 1-8m / 3-26ft recommended
frecuencias de barrido	Pixel clock >162Mhz (UXGA 60hz)
conexión de red	Optional (10 base-T)
Servidor para el visual integrado	Optional DIMM PC available Remote control projector over ethernet via webserver
temperatura ambiente	Max 35°C (95°F)
lámpara	1.75 kW Xenon  Warranty univeral lamphouse: 1000 Hrs

**TECHNICAL SPECIFICATIONS****SLM R9+ PERFORMER**

lentes	Lens	Order nr
	TLD (HB) 0.8	R9842040
	TLD (HB) 1.2	R9840770
	TLD (HB) 1.6 - 2.0	R9842060
	TLD (HB) 2.0 - 2.8	R9842080
	TLD (HB) 2.8 - 5.0	R9842100
	TLD (HB) 5.0 - 8.0	R9842120
desplazamiento de lente	Vertical: -10% to +110% Horizontal: -50% to +50% (small differences occur per lens type)	
Codificadores de lentes	On zoom and focus (with TLD lenses)	
ratio de desplazamiento	Lens	Throw ratio
	TLD (HB) 0.8	0.75
	TLD (HB) 1.2	1.1
	TLD (HB) 1.6 - 2.0	1.45 - 1.85
	TLD (HB) 2.0 - 2.8	1.85 - 2.55
	TLD (HB) 2.8 - 5.0	2.55 - 4.55
	TLD (HB) 5.0 - 8.0	4.55 - 7.3
	TLD+ (HB) 7.5 - 11.2	7.5 - 11.2
ScenergiX	Standard horizontal and vertical electronic edge blending	
núcleo DLP? estanco	Standard	
Filtros de polvo	Dense, high quality microfilters available as spare kit, in a 6-pack & 24-pack	
nivel de ruido	61 dBA (at 40°C)	
Tensión de red	200-240 V	
consumo de potencia	2250 W	
disipación de potencia	Max 6830 BTU/h	
corriente alterna	190V -255V (50Hz -60Hz)	
peso	56 kg (124 lbs)	
dimensiones	WxLxH 585 x 876 x 429 mm (23.0 x 34.5 x 19.9 inch)	
regulación de seguridad	Compliant with UL1950 and EN60950	
interferencia electromagnética	Complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A	
información de pedido	Projector: R9010320 Spare lamp: R9841810 6-pack dust filters: R8454096K 24-pack dust filters: R84540924K	

**Generado en: 24 Feb 2021**Las especificaciones técnicas pueden estar sujetas a cambios sin previo aviso. Consulte [www.barco.com](http://www.barco.com) para obtener la información más actual.