

Galaxy NH-12

Projecteur stéréoscopique à trois puces DLP 12000 lumens , HD 1080p,
réseau-centrique



SPÉCIFICATIONS TECHNIQUES**GALAXY NH-12**

Light output	12,000 center lumens (+/-10%)
Contrast ratio	2,000:1
Resolution	Full 1080p HD
Chip type	Three-chip DLP
Lamp	2kW xenon
Lamp lifetime (typical)	750h warranted, max. 1000h
Weight	70kg (154.2lbs) net / 85kg (187.4lbs) shipping weight
Dimensions (WxLxH)	590x913x345mm / 23.22x35.94x13.58"
Lens range	<ul style="list-style-type: none">■ Horizontal shift up to +/- 65%■ Vertical shift up to +/- 100%
Standard inputs	<ul style="list-style-type: none">■ 1x 5-BNC (RGBHV, RGBS or RGBsB)■ 1x composite video (BNC)■ 1x S-video (4-pin mini DIN)■ 1x DVI■ 1x VGA (D15)
Stereo Inputs	Stereo input layer
Optional Inputs	<ul style="list-style-type: none">■ SD/HD-SDI output
Communication Port	<ul style="list-style-type: none">■ RS-232 (on D9)■ IR or wired remote■ 10/100 Mb/s Ethernet (on RJ45)
Video	<ul style="list-style-type: none">■ PAL, SECAM and NTSC signals■ Composite, S-video, component or RGB formats■ All current HDTV standards (720i, 720p, 1080i, 1080p)
Data	<ul style="list-style-type: none">■ All computer graphics formats up to QXGA at 75Hz■ Analog sources with a pixel clock of up to 270MHz■ DVI sources with a pixel clock of up to 165MHz
Safety	<ul style="list-style-type: none">■ ETL60950 and EN60950■ CE compliant■ CCC compliant
AC power	200 -240 VAC / 50-60Hz
Max. power consumption	2,800 Watt / 9,560 BTU
Special Features	<ul style="list-style-type: none">■ Passive, active and Infitec stereo capabilities■ Source and PIP operation through Windows OS■ Keystone and linearity correction■ Full geometry correction■ Sealed, liquid-cooled engine■ Desktop output including external source windows on DVI-D

Crée le : 21 Jan 2018

Les spécifications techniques sont susceptibles d'être modifiées sans préavis. Veuillez consulter les dernières informations disponibles sur www.barco.com.