

# iQ Praxis G300



**SPECIFICHE TECNICHE****IQ PRAXIS G300**

<b>Emissione luminosa</b>	3,500 ANSI lumen
<b>Uniformità della luminosità</b>	Brightness uniformity: >95 % for the total screen
<b>Pannelli LCD</b>	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
<b>Risoluzione</b>	1024 x 768 (native)
<b>Lampada</b>	2x 200 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1500 h/lamp. 1500 hours in Dual Lamp Mode or max. 3000 hours/set in Single Lamp Mode.
<b>Ottiche</b>	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
<b>Dimensioni schermo</b>	From 1-6 m/3-20 ft.
<b>Contrasto</b>	>400 : 1 (full white/full black)
<b>Frequenze di scansione</b>	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
<b>Compatibilità</b>	The IQ Praxis G300 is compatible with: <ul style="list-style-type: none"><li>• All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>• All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>• All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>• Most Macintosh computers</li><li>• Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>• Most computer sources with a pixel clock up to 160 MHz</li><li>• DVI sources up to SXGA</li></ul>
<b>Ingressi</b>	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video , RGBHV, RGBS, RGsB. 1x Composite Video (BNC) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
<b>Dimensioni (PXLXA)</b>	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
<b>Comunicazione</b>	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
<b>Livello di rumore</b>	
<b>Alimentazione CA</b>	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
<b>Consumo energetico</b>	Max 520 Watt
<b>Dissipazione alimentazione</b>	Max 1775 BTU/h
<b>Peso</b>	Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight: <ul style="list-style-type: none"><li>• without lens max.17.5 kg / 38.5 lbs.</li><li>• with lens: max.20 kg / 44 lbs.</li></ul>
<b>Spostamento obiettivo</b>	QVD Lenses Motorized V shift: -30% +120%

**Generato il: 21 Jan 2018**

Le informazioni e i dati forniti riguardano l'apparecchiatura descritta. Tuttavia ogni singolo articolo è soggetto a modifiche senza preavviso.<br /> L'ultima versione di questo opuscolo è disponibile all'indirizzo [www.barco.com](http://www.barco.com).