

# iQ R200L



**SPECIFICHE TECNICHE****IQ R200L**

<b>Emissione luminosa</b>	1,800 ANSI lumen
<b>Uniformità della luminosità</b>	Brightness uniformity: >95 % for the total screen
<b>Pannelli LCD</b>	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1366 x 1024 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
<b>Risoluzione</b>	1366 x 1024 (native)
<b>Lampada</b>	2x 120 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 6000 h/lamp. 6000 hours in Dual Lamp Mode or max. 12000 hours/set in Single Lamp Mode.
<b>Obiettivi disponibili</b>	<ul style="list-style-type: none"><li>· Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (Long throw).</li><li>· Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width.</li></ul>
<b>Larghezza schermo consigliata</b>	From 1-6 m/3-20 ft.
<b>Rapporto di contrasto</b>	>400 : 1 (full white/full black)
<b>Frequenze di scansione</b>	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
<b>Caratteristiche speciali</b>	<ul style="list-style-type: none"><li>· Standard cable basket</li><li>· Standard light shutter</li><li>· Advanced digital zoom</li><li>· Advanced picture-in-picture</li><li>· Seamless switching with effects</li></ul>
<b>Compatibilità</b>	<ul style="list-style-type: none"><li>-All video sources (PAL, SECAM, NTSC 3.58, NTSC 4.43) in composite, s-VHS, component</li><li>-All currently proposed HDTV extended and improved television standards (1080i, 720p...)</li><li>-All computer graphics formats from VGA, S-VGA, XGA, S-XGA to U-XGA</li><li>-Most Macintosh computers</li><li>-Electronic Workstations with a resolution of up to 1600x1200 at 75Hz</li><li>-Most sources with a pixel clock up to 160MHz</li><li>-DVI sources up to SXGA</li></ul>
<b>Ingressi</b>	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
<b>Comunicazione</b>	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
<b>Livello di rumore</b>	
<b>Alimentazione CA</b>	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
<b>Consumo energetico</b>	Max 350 Watt
<b>Dissipazione alimentazione</b>	
<b>Norme di sicurezza</b>	Compliant with UL1950 and EN60950
<b>Interferenza elettromagnetica</b>	BARCO's iQ Series complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
<b>Peso</b>	Net weight: Body only 12.9 kg/ 28.5 lbs Shipping weight: without lens max. 17.5 kg / 38.5 lbs with lens max. 20 kg / 44 lbs

Generato il: 21 Jan 2018

Le informazioni e i dati forniti riguardano l'apparecchiatura descritta. Tuttavia ogni singolo articolo è soggetto a modifiche senza preavviso.<br /> L'ultima versione di questo opuscolo è disponibile all'indirizzo [www.barco.com](http://www.barco.com).