

# iQ Pro R400

Barco's networked LCD projector with SXGA+ resolution and an amazing brightness level of 4,000 ANSI lumens.



## SPECIFICHE TECNICHE

## IQ PRO R400

Emissione luminosa	4,000 ANSI lumen
Uniformità della luminosità	>95 % for the total screen
Rapporto di contrasto	>400 : 1 (full white/full black)
Pannelli LCD	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1366 x 1024 pixels (aspect ratio 4:3).
Risoluzione	1366 x 1024 (native)
Connessione in rete	iQ Pro Server Specifications: -Processing Power: Pentium III socket with 1,2 Gigahertz Tualatin Celeron processor - Memory: 256 MB RAM -Storage: 40 GB hard disk -Video memory up to 64 MB -Inputs and outputs <ul style="list-style-type: none"><li>PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...</li><li>RJ45 connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)</li><li>4 USB connectors</li><li>Audio: 3,5 mm jacks for Microphone in, Line in and Line out</li></ul>
Compatibilità	The iQ Pro R400 is compatible with: <ul style="list-style-type: none"><li>All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>Most Macintosh computers</li><li>Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>Most computer sources with a pixel clock up to 160 MHz DVI sources up to SXGA</li></ul>
Caratteristiche	- Advanced picture-in-picture - Seamless switching with effects - Standard cable basket - Standard light shutter - Advanced digital zoom
Dimensioni schermo	From 1-6 m/3-20 ft.
Ingressi	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGB. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
Lampada	2x 250 Watt UHP lamp, in lamp housing Typical lifetime: 1000 h/lamp. 1000 hours in Dual Lamp Mode or max. 2000 hours/set in Single Lamp Mode
Ottiche	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width
Frequenze di scansione	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
Spostamento obiettivo	V shift: -30% +120%
Dimensioni (PXLXA)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
Peso	Net weight, body only: 12.9kg/28.5 lbs.
Comunicazione	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Livello di rumore	
Alimentazione CA	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Consumo energetico	Max 650 Watt
Dissipazione alimentazione	Max 2219 BTU/h
Commutazione continua	Standard

Generato il: 21 Jan 2018

Le informazioni e i dati forniti riguardano l'apparecchiatura descritta. Tuttavia ogni singolo articolo è soggetto a modifiche senza preavviso. <br /> L'ultima versione di questo opuscolo è disponibile all'indirizzo [www.barco.com](http://www.barco.com).