

# iQ Pro R300



**SPECIFICHE TECNICHE****IQ PRO R300**

---

<b>Emissione luminosa</b>	3,300 ANSI lumen
<b>Uniformità della luminosità</b>	>95 % for the total screen
<b>Rapporto di contrasto</b>	>400 : 1 (full white/full black)
<b>Pannelli LCD</b>	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1366 x 1024 pixels (aspect ratio 4:3).
<b>Risoluzione</b>	1366 x 1024 (native)
<b>Connessione in rete</b>	<p>iQ Pro Server Specifications: -Processing Power: Pentium III socket with 1,2 Gigahertz Tualatin Celeron processor -Memory: 256 MB RAM -Storage: 40 GB hard disk -Video memory up to 64 MB -Inputs and outputs</p> <ul style="list-style-type: none"><li>■ PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ... RJ45 connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s) 4 USB connectors Audio: 3,5 mm jacks for Microphone in, Line in and Line out</li></ul>
<b>Caratteristiche</b>	<ul style="list-style-type: none"><li>■ Advanced picture-in-picture Seamless switching with effects Standard cable basket Standard light shutter Advanced digital zoom</li></ul>
<b>Compatibilità</b>	<p>The iQ Pro R300 is compatible with:</p> <ul style="list-style-type: none"><li>■ All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>■ All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>■ All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>■ Most Macintosh computers</li><li>■ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>■ Most computer sources with a pixel clock up to 160 MHz DVI sources up to SXGA</li></ul>
<b>Dimensioni schermo</b>	From 1-6 m/3-20 ft.
<b>Ingressi</b>	<p>1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video , RGBHV, RGBS, RGsB.</p> <p>1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board)</p> <p>1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's)</p> <p>1x VGA (D15 connector)</p> <p>1x DVI (Digital Visual Interface)</p>
<b>Lampada</b>	<p>2x 200 Watt UHP lamp, in lamp housing Typical lifetime: 1500 h/lamp. 1500 hours in Dual Lamp Mode or max. 3000 hours/set in Single Lamp Mode</p>

---

**SPECIFICHE TECNICHE****IQ PRO R300**

<b>Ottiche</b>	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width
<b>Frequenze di scansione</b>	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
<b>Spostamento obiettivo</b>	V shift: -30% +120%
<b>Dimensioni (PXLXA)</b>	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
<b>Peso</b>	Net weight, body only: 12.9kg/28.5 lbs.
<b>Comunicazione</b>	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
<b>Livello di rumore</b>	
<b>Alimentazione CA</b>	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
<b>Consumo energetico</b>	Max 550 Watt
<b>Dissipazione alimentazione</b>	Max 1878 BTU/h
<b>Norme di sicurezza</b>	Compliant with UL1950 and EN60950
<b>Interferenza elettromagnetica</b>	BARCO's iQ Pro R300 complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
<b>Commutazione continua</b>	Standard

Generato il: 21 Jan 2018

Le informazioni e i dati forniti riguardano l'apparecchiatura descritta. Tuttavia ogni singolo articolo è soggetto a modifiche senza preavviso.<br /> L'ultima versione di questo opuscolo è disponibile all'indirizzo [www.barco.com](http://www.barco.com).