

# CLM R10+

SXGA+, 10,000 lumens single-chip DLP projector



DMX  
CONTROL

10K  
LUMENS

SXGA+  
1400x1050

**TECHNISCHE SPECIFICATIES****CLM R10+**

Type projector	SXGA+ single-chip DLP digital projector
Technologie	0.95" DMD™ x1 CW:RGBW
Resolutie	1400x1050
Helderheid	10,000 center lumens 9,500 ANSI lumens
Contrastverhouding	1,200:1 (standard) 2,000:1 (high contrast mode)
Helderheidsuniformiteit	95%
Beeldverhouding	4:3
ScenergiX	Horizontal and vertical edge blending
Type lens	QCLD
Lenzen	CLD (fix) 0.85:1 (zoom) 1.2-1.5 1.5-2.2 2.2-4.4 4.4-7.0
Optische lensverschuiving	Vertical: -20% to +110% Horizontal: 15% (L) and 100% (R) on zoom lenses
Kleurcorrectie	P7
Lampen	4x300W
Levensduur lamp	750 hours (typical) 1250 hours (maximum)
Transport met lamp	Yes
Lampbehuizing, snelle vervanging	Yes, auto lamp select
Lampvervanging door klant	N/A
Lampgarantie (vervanging op locatie/in de fabriek)	120 days, 500 hours
Verzegelde DLPTM-kern	Standard
Optische dowser	0-100% brightness control through DMX512 signal
Picture-in-Picture	Two sources simultaneously
Oriëntatie	Table/ceiling/(side)portrait/vertical
DMX 512	Standard
WARP	H keystone
Geïntegreerde webserver	N/A
CLU (constante lichtuitvoer)	N/A
Geschikt voor 3D (optioneel)	Passive, circular polarized
Ingangen	DVI(HDCP); 5-BNC RGBHV (RGBS/RGsB, YUV CS/SOY, Composite video, S-Video)
Optionele ingangen	DVI(HDCP), 5-BNC RGBHV, RGBS/RGsB, YUV CS/SOY, Composite video, S-Video; HDSI/SDI
Max. pixelklok	165 MHz
Softwaretools	Projector Toolset
Controle	XLR wired + IR, RS232
Netwerkverbinding	10/100 base-T, RJ-45 connection

**TECHNISCHE SPECIFICATIES****CLM R10+**

Voedingsvereisten	100-240V / 50-60Hz
Max. energieverbruik	1600W
Geluidsniveau (standaard bij 25°C/77°F)	49dB(A)
Operationele omgevingstemperatuur	0-40°C / 32°-104°F
Operationele vochtigheid	0-80% (non condens)
Dissipatie BTU	max 5459 BTU/h
Afmetingen (B x L x H)	692 x 442 x 293mm 27.24 x 17.4 x 11.53 inches
Gewicht	30kg (66.13lbs)
Verzendingsafmetingen	(LxWxH) 770 x 580 x 480mm 30.31 x 22.83 x 18.89 inches
Verzendgewicht af fabriek	35kg (77.16lbs)
Standaardaccessoires	Power cord, wireless/XLR wired rugged remote control
Certificeringen	Compliant with FCC rules and regulations, part 15 Class A and CE EN55022 Class A, RoHS
Garantie	2 years

Last updated: 24 Feb 2021

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.